

# ChemShield 1185 Resin

(Part A)

Safety Data Sheet (SDS)

**Section 1 - Product and Company Identification** 

Trade Name: ChemShield 1185 Resin (All Versions)

# Company:

Wolverine Coatings Corporation 5969 Highway 221 Roebuck, SC 29376 +1 (864) 587-3144 Product Code: ChemShield 1185-020 BU2A Resin

# **Emergency Contact:**

ChemTel 24 Hr. US Emergency Number: +1 (800) 255-3924 ChemTel 24 Hr. Worldwide Emergency Number: +1 (813) 248-0585

Product Use: Coatings

Not recommended for: None Identified

# **Section 2 - Hazards Identification**

# **GHS Ratings:**

Skin Corrosive	2	Reversible adverse effects in dermal tissue, Draize score: >= 2.3 < 4.0 or persistent inflammation	
Eye Corrosive	2A	Eye irritant: Subcategory 2A, Reversible in 21 days	
Respiratory sensitizer	1	Respiratory sensitizer	
Skin Sensitizer	1	Skin Sensitizer	
Aquatic toxicity	C3	Acute toxicity > 10.0 but <= 100.0 mg/l and lack of rapid degradability and log Kow >= 4 unless BCF < 500 and unless chronic toxicity > 1 mg/l	
GHS Hazards			
H315	Caus	es skin irritation	
H317	May	cause an allergic skin reaction	
H319	Causes serious eye irritation		
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled		
H412	Harmful to aquatic life with long lasting effects		
GHS Precautions			
P261		breathing dust/fume/gas/mist/vapours/spray	
P264	Wash thoroughly after handling		
P272	Contaminated work clothing should not be allowed out of the workplace		
P273	Avoid release to the environment		
P280	Wear protective gloves/protective clothing/eye protection/face protection		
P285	In case of inadequate ventilation wear respiratory protection		
P321	Specific treatment (see label)		
P362		off contaminated clothing and wash before reuse	
P363		contaminated clothing before reuse	
P302+P352	IF ON SKIN: Wash with soap and water		
P304+P341	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing		
P305+P351+P338	IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing		
P332+P313	If skin irritation occurs: Get medical advice/attention		
P333+P313	lf skir	irritation or a rash occurs: Get medical advice/attention	
P337+P313	Get m	nedical advice/attention	
P342+P311	Call a POISON CENTER or doctor/physician		

Signal Word: Danger



# Section 3 - Composition / Information on Ingredients

Chemical Name	CAS number	Weight Concentration %
Quartz	14808-60-7	40.00% - 50.00%
Bisphenol A diglycidyl ether resin	25068-38-6	40.00% - 50.00%
Benzyl Alcohol	100-51-6	1.00% - 5.00%
1,4-Bis(2,3-epoxypropoxy)butane	2425-79-8	1.00% - 5.00%

# **Section 4 - First Aid Measures**

**Inhalation:** If affected, remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.

**Eye Contact:** Immediately flush eyes for at least fifteen minutes with running water. Hold eyelids apart to ensure rinsing of the entire eye surface and lids with water. If eye irritation persists: Get medical advice/attention.

**Skin contact:** Immediately remove contaminated clothing and shoes. Wash affected areas thoroughly with soap and water. If irritation develops, seek medical attention.

**Ingestion:** Do not induce vomiting. Never give anything by mouth to an unconscious person. If a person vomits when lying on his back, place him in the recovery position. Get immediate medical attention.

### **Section 5 - Fire Fighting Measures**

Flash Point:100 C (212 F)LEL: 1.00UEL: 13.00Extinguishing Media:Use carbon dioxide, foam, dry chemical, dry sand, water fog, or limestone powderextinguishing systems.

Unusual Fire and Explosion Hazards: None

**Hazardous combustion products:** Irritating or toxic substances may be emitted upon burning, combustion or decomposition. See section 10 (Stability and Reactivity) for additional information.

**Special Fire Fighting Procedures:** Firefighters should be equipped with self-contained breathing apparatus. **Fire Equipment:** No Data

### **Section 6 - Accidental Release Measures**

**Spill And Leak Procedures:** Avoid all personal contact. Ensure cleanup personnel wear all appropriate Personal Protective Equipment (PPE), including respiratory protection. Spills should be contained, solidified, and placed in suitable containers for disposal.

# Section 7 - Handling and Storage

**Handling Precautions:** Use good laboratory/workplace procedures. Wash thoroughly after handling this product. Always wash up before eating, smoking or using the facilities. Use under well-ventilated conditions.

Avoid eye and skin contact. Avoid inhalation of aerosol, mist, spray, fume or vapor. Avoid drinking, tasting, swallowing or ingesting this product. Wash contaminated clothing before reuse. Discard shoes contaminated with this product.

**Storage Requirements:** Keep away from heat, sparks, and open flames. Store cool and dry, under well-ventilated conditions. Store this material away from incompatible substances (see section 10). Do not store in open, unlabeled or mislabeled containers. Keep container closed when not in use.

Chemical Name / CAS #	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Quartz 14808-60-7	TWA30 mg/m3 / %SiO2+2 total dust TWA: 10 mg/m3 /%SiO2+2 respirable fraction	TWA: 0.025 mg/m3	Not Established
Bisphenol A diglycidyl ether resin 25068-38-6	Not Established	Not Established	Not Established
Benzyl Alcohol 100-51-6	Not Established	Not Established	Not Established
1,4-Bis(2,3-epoxypropoxy) butane 2425-79-8	Not Established	Not Established	Not Established

# **Section 8 - Exposure Controls / Personal Protection**

Ventilation: Good general mechanical ventilation and local exhaust is recommended.

**Hygiene:** Eye wash must be easily accessible. Wear protective clothing as necessary to prevent contact. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. Gloves must be inspected regularly and prior to each use. Replace if necessary.

**Personal Protective Equipment:** Wear impervious protective gloves. Wear OSHA, NIOSH approved organic vapor respirator if ventilation is inadequate. Wear appropriate protective eyewear such as splash-proof, chemical resistant safety goggles.

**Contaminated Gear:** Take off all contaminated clothing immediately. Wash contaminated clothing before reuse.

### **Section 9 - Physical and Chemical Properties**

This mixture typically exhibits the following properties under normal circumstances:

Appearance:	Liquid	Odor:	Not available
Vapor Pressure:	0.072 mm Hg	Odor threshold:	Not available
Vapor Density:	Not available	pH:	Not available
Density (g/cm3):	1.55	Melting point:	Not available
Freezing point:	Not available	Solubility:	Not available
Boiling range:	Not available	Flash point:	100°C, 212°F
Evaporation rate:	Not available	Flammability:	Not available
Explosive Limits:	Not available	Partition coefficient (n- octanol/water):	Not available
Autoignition temperature:	Not available	Decomposition temperature:	Not available
Viscosity:	Not available	Grams VOC less water:	Not available

### Stability:

STABLE

### Components of this mixture are incompatible with the following materials:

Strong Oxidizers Strong Acids Strong Bases Amines Strong Reducing Agents

# This mixture is likely to exhibit the following combustion products:

Carbon Dioxide, Carbon Monoxide Biphenyls Nitrogen Oxides Smoke Aldehydes

Hazardous polymerization will not occur.

### **Section 11 - Toxicological Information**

#### Mixture Toxicity:

Inhalation Toxicity LC50: 1,115mg/L

# **Component Toxicity:**

	icy.		
100-51-6	Benzyl Alcohol		
	Oral LD50: 1,62	20 mg/kg (Rat) Derr	nal LD50: 2,010 mg/kg (Rabbit) Inhalation LC50: 4 mg/L (
2425-79-8	1,4-Bis(2,3-epo	xypropoxy)butane	
	Oral LD50: 1,16	63 mg/kg (rat) Derm	al LD50: 1,130 mg/kg (rabbit) Inhalation LC50: 250 ppm
Routes of Entry:			
Inhalation	Skin Contact	Eye Contact	Ingestion

# Exposure to this material may affect the following organs:

Lungs Respiratory System

The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing):

CAS Number	Description	<u>% Weight</u>	Carcinogen Rating
14808-60-7	Quartz	40 to 50%	Quartz: If product is in liquid or paste form, physical or health hazards listed related to dust are not considered significant. However, product may contain substances that could be potential hazards if caused to become airborne due to grinding, sanding or other abrasive processes.

# Section 12 - Ecological Information

Component Ecotoxicity:	
Quartz	LC50 >10,000 mg/l fish 72h; EC50 7600 mg/L water flea 48h; EC50 440mg/L algae, 72h;
Bisphenol A diglycidyl ether resin	LC50 3.1 mg/l fish 96h; EC50 2.1 mg/l water flea 48h; EC50 >11mg/l Algae 72h; LC50 >100mg/l bacteria 3h
Benzyl Alcohol	LC50 460 mg/l fish 96 h; EC50 360 ppm water flea 48 h; EC50 640 mg/l algae 96 h; EC10 658 mg/l bacteria 16 h

SDS:	ChemShield 1185 Resin

# **Section 13 - Disposal Considerations**

Waste disposal Methods: Dispose in accordance with Federal, State and Local regulations.

### **Section 14 - Transport Information**

This material is classified for transport as follows:

### Agency Proper Shipping Name

DOT Non-Regulated IATA IMDG UN NumberPacking GroupHazard ClassN/AN/AN/A

# **Section 15 - Regulatory Information**

### Additional regulatory listings, where applicable:

# State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

WARNING! This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

Quartz 14808-60-7

### Materials not included on the Canada DSL inventory:

- None

**Commonwealth of Massachusetts "Right to Know":** This product contains the following toxic or hazardous substances which appear on the Massachusetts Substance List:

Benzyl Alcohol 100-51-6 Quartz 14808-60-7

**NJ "Right to Know":** This product contains the following toxic or hazardous substances which appear on the New Jersey Substance List:

Benzyl Alcohol 100-51-6 Bisphenol A diglycidyl ether resin 25068-38-6 Quartz 14808-60-7

**Pennsylvania "Right to Know":** This product contains the following toxic or hazardous substances which appear on the Pennsylvania Substance List:

Benzyl Alcohol 100-51-6 Bisphenol A diglycidyl ether resin 25068-38-6 Quartz 14808-60-7

# EPA SARA Title III Section 313 (40 CFR 372) components above 'de minimum' level:

- None

**Toxic Substances Control Act (TSCA):** All chemicals except those listed below appear in the Toxic Substances Control Act Chemical Substance Inventory:

- None

### <u>Country</u>

<u>Regulation</u>

**All Components Listed** 

### EU Risk Phrases

### Safety Phrase

Toxic Substances Control Act (TSCA): All chemicals except those listed below appear in the Toxic Substances

Control Act Chemical Substance Inventory:

- None

### EPA SARA Title III Section 313 (40 CFR 372) compnenets above 'de minimum' level:

### **Section 16 - Other Information**

For further information, please contact the Product Safety director. The information and recommendations contained herein are, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. All chemicals may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Final determination of suitability of the chemical is the sole responsibility of the user. Users of any chemical should satisfy themselves that the conditions and methods of use assure that the chemical is used safely. No representations or warranties, either expressed or implied of merchantability, fitness for a particular purpose, or any other nature, are made hereunder with respect to the information contained herein, or to the chemical to which the user refers.

Date Revised: 2019-11-25

Revision #: 1