

ChemShield 1633 Resin

(Part A)

Safety Data Sheet (SDS)

Section 1 - Product and Company Identification

Trade Name: ChemShield 1633 Resin (All Versions) Product (

Company:

Wolverine Coatings Corporation 5969 Highway 221 Roebuck, SC 29376 +1 (864) 587-3144

Product Use: Coatings

Product Code: ChemShield 1633-000 WH4A

Emergency Contact:

ChemTel 24 Hr. US Emergency Number:

+1 (800) 255-3924

ChemTel 24 Hr. Worldwide Emergency Number:

+1 (813) 248-0585

Not recommended for: None Identified

Section 2 - Hazards Identification

GHS Ratings:

Skin Corrosive 2 Reversible adverse effects in dermal tissue, Draize score: >= 2.3 < 4.0

or persistent inflammation

Eye Corrosive 2A Eye irritant: Subcategory 2A, Reversible in 21 days

Skin Sensitizer 1 Skin Sensitizer

Mutagen 1B Known to produce heritable mutations in human germ

cellsSubcategory 1B, Positive results: In vivo heritable germ cell tests in mammals, Human germ cell tests, In vivo somatic mutagenicity tests, combined with some evidence of germ cell mutagenicity

Carcinogen 1A Known Human Carcinogen Based on human evidence

GHS Hazards

H315 Causes skin irritation

H317 May cause an allergic skin reaction

H319 Causes serious eye irritation H340 May cause genetic defects

H350 May cause cancer

GHS Precautions

P201 Obtain special instructions before use

P202 Do not handle until all safety precautions have been read and understood

P261 Avoid breathing dust/fume/gas/mist/vapours/spray

P264 Wash thoroughly after handling

P272 Contaminated work clothing should not be allowed out of the workplace P280 Wear protective gloves/protective clothing/eye protection/face protection

P281 Use personal protective equipment as required

P321 Specific treatment (see label)

P362 Take off contaminated clothing and wash before reuse

P363 Wash contaminated clothing before reuse P302+P352 IF ON SKIN: Wash with soap and water

P305+P351+P338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact

lenses if present and easy to do – continue rinsing

P308+P313 IF exposed or concerned: Get medical advice/attention P332+P313 If skin irritation occurs: Get medical advice/attention

P333+P313 If skin irritation or a rash occurs: Get medical advice/attention

P337+P313 Get medical advice/attention

P405 Store locked up

Signal Word: Danger



Section 3 - Composition / Information on Ingredients

Chemical Name	CAS number	Weight Concentration %
Epoxy Phenol Novalac Resin	28064-14-4	30.00% - 40.00%
Quartz	14808-60-7	30.00% - 40.00%
Titanium dioxide	1317-80-2	5.00% - 10.00%
Titanium Dioxide	13463-67-7	5.00% - 10.00%
Trade Secret		5.00% - 10.00%
Benzyl Alcohol	100-51-6	1.00% - 5.00%
Ethylbenzene	100-41-4	0.10% - 1.00%

Section 4 - First Aid Measures

Inhalation: If affected, remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.

Eye Contact: Immediately flush eyes for at least fifteen minutes with running water. Hold eyelids apart to ensure rinsing of the entire eye surface and lids with water. If eye irritation persists: Get medical advice/attention.

Skin contact: Immediately remove contaminated clothing and shoes. Wash affected areas thoroughly with soap and water. If irritation develops, seek medical attention.

Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious person. If a person vomits when lying on his back, place him in the recovery position. Get immediate medical attention.

Section 5 - Fire Fighting Measures

Flash Point: 175 C (346 F) LEL: 1.00 UEL: 13.00

Extinguishing Media: Use carbon dioxide, foam, dry chemical, dry sand, water fog, or limestone powder extinguishing systems.

Unusual Fire and Explosion Hazards: None

Hazardous combustion products: Irritating or toxic substances may be emitted upon burning, combustion or decomposition. See section 10 (Stability and Reactivity) for additional information.

Special Fire Fighting Procedures: Firefighters should be equipped with self-contained breathing apparatus.

Fire Equipment: No Data

Section 6 - Accidental Release Measures

Spill And Leak Procedures: Avoid all personal contact. Ensure cleanup personnel wear all appropriate Personal Protective Equipment (PPE), including respiratory protection. Spills should be contained, solidified, and

Section 7 - Handling and Storage

Handling Precautions: Use good laboratory/workplace procedures. Wash thoroughly after handling this product. Always wash up before eating, smoking or using the facilities. Use under well-ventilated conditions. Avoid eye and skin contact. Avoid inhalation of aerosol, mist, spray, fume or vapor. Avoid drinking, tasting, swallowing or ingesting this product. Wash contaminated clothing before reuse. Discard shoes contaminated with this product.

Storage Requirements: Keep away from heat, sparks, and open flames. Store cool and dry, under well-ventilated conditions. Store this material away from incompatible substances (see section 10). Do not store in open, unlabeled or mislabeled containers. Keep container closed when not in use.

Section 8 - Exposure Controls / Personal Protection

Chemical Name / CAS #	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Epoxy Phenol Novalac Resin 28064-14-4	Not Established	Not Established	Not Established
Quartz 14808-60-7	TWA30 mg/m3 / %SiO2+2 total dust TWA: 10 mg/m3 /%SiO2+2 respirable fraction	TWA: 0.025 mg/m3	Not Established
Titanium dioxide 1317-80-2	Not Established	Not Established	Not Established
Titanium Dioxide 13463-67-7	TWA: 15 mg/m3	TWA: 10 mg/m3	Not Established
Trade Secret	Not Established	Not Established	Not Established
Benzyl Alcohol 100-51-6	Not Established	Not Established	Not Established
Ethylbenzene 100-41-4	TWA: 435 mg/m3	TWA: 20 ppm	Not Established

Ventilation: Good general mechanical ventilation and local exhaust is recommended.

Hygiene: Eye wash must be easily accessible. Wear protective clothing as necessary to prevent contact. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. Gloves must be inspected regularly and prior to each use. Replace if necessary.

Personal Protective Equipment: Wear impervious protective gloves. Wear OSHA, NIOSH approved organic vapor respirator if ventilation is inadequate. Wear appropriate protective eyewear such as splash-proof, chemical resistant safety goggles.

Contaminated Gear: Take off all contaminated clothing immediately. Wash contaminated clothing before reuse.

Section 9 - Physical and Chemical Properties

This mixture typically exhibits the following properties under normal circumstances:

Appearance:	Liquid	Odor:	Not available
Vapor Pressure:	3.9 mm Hg	Odor threshold:	Not available
Vapor Density:	Not available	pH:	Not available

Density (g/cm3): 1.63 Melting point: Not available Freezing point: Not available Solubility: Not available 174°C, 346°F **Boiling range:** Not available Flash point: **Evaporation rate:** Not available Flammability: Not available **Explosive Limits:** Not available Partition coefficient (n-Not available octanol/water): Autoignition Not available Decomposition Not available temperature: temperature: Viscosity: Not available Grams VOC less water: Not available

Section 10 - Stability and Reactivity

Stability:

STABLE

Components of this mixture are incompatible with the following materials:

Strong Acids

Strong Oxidizers

Organic Acids

Mineral Acids

Peroxides

Sodium Hypochlorite

Amines

Alkalies

This mixture is likely to exhibit the following combustion products:

Carbon Dioxide, Carbon Monoxide

Nitrogen Oxides

Ammonia

Biphenyls

Phenol

Hazardous polymerization will not occur.

Section 11 - Toxicological Information

Mixture Toxicity:

Oral Toxicity LD50: 4,085mg/kg Inhalation Toxicity LC50: 404mg/L

Component Toxicity:

28064-14-4 Epoxy Phenol Novalac Resin

Oral LD50: 2,000 mg/kg (rat)

13463-67-7 Titanium Dioxide

Inhalation LC50: 7 mg/kg (Rat)

100-51-6 Benzyl Alcohol

Oral LD50: 1,620 mg/kg (Rat) Dermal LD50: 2,010 mg/kg (Rabbit) Inhalation LC50: 4 mg/L (

100-41-4 Ethylbenzene

Oral LD50: 3,500 mg/kg (rat) Inhalation LC50: 17 mg/L (rat)

Routes of Entry:

Inhalation Skin Contact Eye Contact Ingestion

Exposure to this material may affect the following organs:

Lungs Respiratory System

The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing):

<u>CAS Number</u> <u>Description</u> <u>% Weight</u> <u>Carcinogen Rating</u>

1317-80-2 Titanium dioxide 5 to 10% Titanium dioxide: 100-41-4 Ethylbenzene 0.1 to 1.0% Ethylbenzene: 14808-60-7 Quartz 30 to 40% Quartz: If product

Quartz: If product is in liquid or paste form, physical or health hazards listed related to dust are not considered significant. However, product may contain substances that could be potential hazards if caused to become airborne due to grinding, sanding or other

abrasive processes.

Section 12 - Ecological Information

Component Ecotoxicity:

Epoxy Phenol Novalac Resin LC50 10 mg/l fish 96h; EC50 10 mg/l water flea 48h

Quartz LC50 >10,000 mg/l fish 72h; EC50 7600 mg/L water flea 48h; EC50

440mg/L algae, 72h;

Titanium Dioxide LC50 >1000 mg/l fish 96h; EC50 >1000 mg/l water flea 48h; EC50 >100

mg/l algae 72h

Benzyl Alcohol LC50 460 mg/l fish 96 h; EC50 360 ppm water flea 48 h; EC50 640 mg/l

algae 96 h; EC10 658 mg/l bacteria 16 h

Ethylbenzene LC50 5.1 mg/l fish 96h; EC50 2.4 mg/l water flea 96h; EC50 4.9 mg/l algae

72h

Section 13 - Disposal Considerations

Waste disposal Methods: Dispose in accordance with Federal, State and Local regulations.

Section 14 - Transport Information

This material is classified for transport as follows:

AgencyProper Shipping NameUN NumberPacking GroupHazard ClassDOTNon-RegulatedNANA

IATA No Data
IMDG No Data

Section 15 - Regulatory Information

Additional regulatory listings, where applicable:

State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

WARNING! This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

Ethylbenzene 100-41-4 Titanium Dioxide 13463-67-7

Quartz 14808-60-7

Materials not included on the Canada DSL inventory:

- None

Commonwealth of Massachusetts "Right to Know": This product contains the following toxic or hazardous substances which appear on the Massachusetts Substance List:

Ethylbenzene 100-41-4 Benzyl Alcohol 100-51-6 Titanium Dioxide 13463-67-7

Quartz 14808-60-7

NJ "Right to Know": This product contains the following toxic or hazardous substances which appear on the New Jersey Substance List:

Ethylbenzene 100-41-4 Benzyl Alcohol 100-51-6 Titanium Dioxide 13463-67-7 Titanium dioxide 1317-80-2 Quartz 14808-60-7

Pennsylvania "Right to Know": This product contains the following toxic or hazardous substances which appear on the Pennsylvania Substance List:

Ethylbenzene 100-41-4 Benzyl Alcohol 100-51-6 Titanium Dioxide 13463-67-7 Titanium dioxide 1317-80-2 Quartz 14808-60-7

EPA SARA Title III Section 313 (40 CFR 372) components above 'de minimum' level:

Ethylbenzene 100-41-4

Toxic Substances Control Act (TSCA): All chemicals except those listed below appear in the Toxic Substances Control Act Chemical Substance Inventory:

- None

Country Regulation

All Components Listed

EU Risk Phrases

Safety Phrase

Toxic Substances Control Act (TSCA): All chemicals except those listed below appear in the Toxic Substances Control Act Chemical Substance Inventory:

- None

EPA SARA Title III Section 313 (40 CFR 372) compnenets above 'de minimum' level:

Section 16 - Other Information

For further information, please contact the Product Safety director. The information and recommendations contained herein are, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. All chemicals may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Final determination of suitability of the chemical is the sole responsibility of the user. Users of any chemical should satisfy themselves that the conditions and methods of use assure that the chemical is used safely. No representations or warranties, either expressed or implied of merchantability, fitness for a particular purpose, or any other nature, are made hereunder with respect to the information contained herein, or to the chemical to which the user refers.

Date Revised: 2019-11-25 Revision #: 1