

ColorMeld 5280 GY2A

(Colorant)

Safety Data Sheet (SDS)

Section 1 - Product and Company Identification

Trade Name: ColorMeld 5280 GY2A (All Versions)

Company:

Wolverine Coatings Corporation 5969 Highway 221 Roebuck, SC 29376 +1 (864) 587-3144

Product Use: Coatings

Product Code: ColorMeld 5280 GY2A Resin

Emergency Contact:

ChemTel 24 Hr. US Emergency Number: +1 (800) 255-3924 ChemTel 24 Hr. Worldwide Emergency Number:

+1 (813) 248-0585

Not recommended for: None Identified

Section 2 - Hazards Identification

GHS Ratings:

GHS Hazards

GHS Precautions

Signal Word:

There are no GHS ratings that apply to this product at this time.

Section 3 - Composition / Information on Ingredients

Chemical Name	CAS number	Weight Concentration %
Titanium Dioxide	13463-67-7	40.00% - 50.00%
Amorphous Silica	112926-00-8	5.00% - 10.00%
Aluminum Hydroxide	21645-51-2	5.00% - 10.00%
Carbon mesoporous	1333-86-4	1.00% - 5.00%

Section 4 - First Aid Measures

SDS: ColorMeld 5280 GY2A

Inhalation: If affected, remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.

Eye Contact: Immediately flush eyes for at least fifteen minutes with running water. Hold eyelids apart to ensure rinsing of the entire eye surface and lids with water. If eye irritation persists: Get medical advice/attention.

Skin contact: Immediately remove contaminated clothing and shoes. Wash affected areas thoroughly with soap and water. If irritation develops, seek medical attention.

Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious person. If a person vomits when lying on his back, place him in the recovery position. Get immediate medical attention.

Section 5 - Fire Fighting Measures

Flash Point: N/A LEL: UEL:

Extinguishing Media: Use carbon dioxide, foam, dry chemical, dry sand, water fog, or limestone powder

extinguishing systems.

Unusual Fire and Explosion Hazards: None

Hazardous combustion products: Irritating or toxic substances may be emitted upon burning, combustion or decomposition. See section 10 (Stability and Reactivity) for additional information.

Special Fire Fighting Procedures: Firefighters should be equipped with self-contained breathing apparatus.

Fire Equipment: No Data

Section 6 - Accidental Release Measures

Spill And Leak Procedures: Avoid all personal contact. Ensure cleanup personnel wear all appropriate Personal Protective Equipment (PPE), including respiratory protection. Spills should be contained, solidified, and placed in suitable containers for disposal.

Section 7 - Handling and Storage

Handling Precautions: Use good laboratory/workplace procedures. Wash thoroughly after handling this product. Always wash up before eating, smoking or using the facilities. Use under well-ventilated conditions. Avoid eye and skin contact. Avoid inhalation of aerosol, mist, spray, fume or vapor. Avoid drinking, tasting, swallowing or ingesting this product. Wash contaminated clothing before reuse. Discard shoes contaminated with this product.

Storage Requirements: Keep away from heat, sparks, and open flames. Store cool and dry, under well-ventilated conditions. Store this material away from incompatible substances (see section 10). Do not store in open, unlabeled or mislabeled containers. Keep container closed when not in use.

Section 8 - Exposure Controls / Personal Protection

Chemical Name / CAS #	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Titanium Dioxide 13463-67-7	TWA: 15 mg/m3	TWA: 10 mg/m3	Not Established
Amorphous Silica 112926-00-8	OEL-TWA: 80 mg/m3	Not Established	Not Established
Aluminum Hydroxide 21645-51-2	Not Established	Not Established	Not Established
Carbon mesoporous 1333-86-4	OEL-TWA: 3.5 mg/m3	TLV-TWA: 3.5 mg/m3	Not Established

Ventilation: Good general mechanical ventilation and local exhaust is recommended.

Hygiene: Eye wash must be easily accessible. Wear protective clothing as necessary to prevent contact. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. Gloves must be inspected regularly and prior to each use. Replace if necessary.

Personal Protective Equipment: Wear impervious protective gloves. Wear OSHA, NIOSH approved organic vapor respirator if ventilation is inadequate. Wear appropriate protective eyewear such as splash-proof, chemical resistant safety goggles.

Contaminated Gear: Take off all contaminated clothing immediately. Wash contaminated clothing before reuse.

Section 9 - Physical and Chemical Properties

This mixture typically exhibits the following properties under normal circumstances:

Appearance:	Liquid	Odor:	Not available
Vapor Pressure:	N/A	Odor threshold:	Not available
Vapor Density:	Not available	pH:	Not available
Density (g/cm3):	1.85	Melting point:	Not available
Freezing point:	Not available	Solubility:	Not available
Boiling range:	Not available	Flash point:	999 C, 999 F
Evaporation rate:	Not available	Flammability:	Not available
Explosive Limits:	Not available	Partition coefficient (n- octanol/water):	Not available
Autoignition temperature:	Not available	Decomposition temperature:	Not available
Viscosity:	Not available	Grams VOC less water:	Not available

Section 10 - Stability and Reactivity

Stability:

STABLE

Components of this mixture are incompatible with the following materials:

Strong Oxidizers Strong Acids

This mixture is likely to exhibit the following combustion products:

Carbon Dioxide, Carbon Monoxide

Hazardous polymerization will not occur.

Section 11 - Toxicological Information

Mixture Toxicity:

Inhalation Toxicity LC50: 31mg/L

Component Toxicity:

13463-67-7 Titanium Dioxide

Inhalation LC50: 7 mg/kg (Rat)

21645-51-2 Aluminum Hydroxide

Oral LD50: 2,000 mg/kg (rat)

1333-86-4 Carbon mesoporous

Dermal LD50: 3,000 mg/kg (rabbit)

Routes of Entry:

Inhalation Skin Contact Eye Contact Ingestion

Exposure to this material may affect the following organs:

No Data

The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing):

<u>CAS Number</u> <u>Description</u> <u>% Weight</u> <u>Carcinogen Rating</u>

N/A

Carbon mesoporous: If product is in liquid or paste form, physical or health hazards listed related to dust are not considered significant. However, product may contain substances that could be potential hazards if caused to become airborne due to grinding, sanding or other abrasive processes.

UN Number Packing Group Hazard Class

N/A

N/A

Section 12 - Ecological Information

Component Ecotoxicity:

Titanium Dioxide LC50 >1000 mg/l fish 96h; EC50 >1000 mg/l water flea 48h; EC50 >100

mg/l algae 72h

Carbon mesoporous LC50 1000 mg/l fish 96h; EC50 5600 mg/l water flea 24h; EC50 10000

mg/l algae 72h

Section 13 - Disposal Considerations

Waste disposal Methods: Dispose in accordance with Federal, State and Local regulations.

Section 14 - Transport Information

This material is classified for transport as follows:

Proper Shipping Name Agency

Non-Regulated DOT

IATA **IMDG**

Section 15 - Regulatory Information

Additional regulatory listings, where applicable:

State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

WARNING! This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

Carbon mesoporous 1333-86-4 Titanium Dioxide 13463-67-7

Materials not included on the Canada DSL inventory:

- None

Commonwealth of Massachusetts "Right to Know": This product contains the following toxic or hazardous substances which appear on the Massachusetts Substance List:

Carbon mesoporous 1333-86-4 Amorphous Silica 112926-00-8 Titanium Dioxide 13463-67-7

NJ "Right to Know": This product contains the following toxic or hazardous substances which appear on the New Jersey Substance List:

Carbon mesoporous 1333-86-4 Aluminum Hydroxide 21645-51-2 Amorphous Silica 112926-00-8 Titanium Dioxide 13463-67-7

SDS: ColorMeld 5280 GY2A

Pennsylvania "Right to Know": This product contains the following toxic or hazardous substances which appear on the Pennsylvania Substance List:

Carbon mesoporous 1333-86-4 Amorphous Silica 112926-00-8 Aluminum Hydroxide 21645-51-2 Titanium Dioxide 13463-67-7

EPA SARA Title III Section 313 (40 CFR 372) components above 'de minimum' level:

- None

Toxic Substances Control Act (TSCA): All chemicals except those listed below appear in the Toxic Substances Control Act Chemical Substance Inventory:

- None

<u>Country</u> <u>Regulation</u>

All Components Listed

EU Risk Phrases

Safety Phrase

Toxic Substances Control Act (TSCA): All chemicals except those listed below appear in the Toxic Substances Control Act Chemical Substance Inventory:

- None

EPA SARA Title III Section 313 (40 CFR 372) compnenets above 'de minimum' level:

Section 16 - Other Information

SDS: ColorMeld 5280 GY2A

For further information, please contact the Product Safety director. The information and recommendations contained herein are, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. All chemicals may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Final determination of suitability of the chemical is the sole responsibility of the user. Users of any chemical should satisfy themselves that the conditions and methods of use assure that the chemical is used safely. No representations or warranties, either expressed or implied of merchantability, fitness for a particular purpose, or any other nature, are made hereunder with respect to the information contained herein, or to the chemical to which the user refers.

Date Revised: 2019-11-25 Revision #: 1