

IntegraFlex 1923 Resin

(Part A)

Safety Data Sheet (SDS)

Section 1 - Product and Company Identification

Trade Name: IntegraFlex 1923 Resin (All Versions)

Company:

Wolverine Coatings Corporation 5969 US Highway 221 Roebuck, SC 29376 +1 (864) 587-3144

Product Use: Coatings

Product Code: 1923-020-NU2A-01-RES

Emergency Contact:

ChemTel 24 Hr. US Emergency Number:

+1 (800) 255-3924

ChemTel 24 Hr. Worldwide Emergency Number:

+1 (813) 248-0585

Not Recommended For: None Identified

Section 2 - Hazards Identification

GHS Ratings:

Skin corrosion/irritation	2	Reversible adverse effects in dermal tissue, Draize score: >= 2.3 < 4.0 or persistent inflammation
Serious eye	1	Serious eye damage: Irreversible damage 21 days after exposure,
damage/eye irritation		Draize score: Corneal opacity >= 3, Iritis > 1.5
Skin sensitization	1	Skin Sensitizer
Germ cell mutagenicity	2	Suspected/Possible: May include heritable mutations in human germ cells, Positive evidence from tests in mammals and somatic cell tests, In vivo somatic genotoxicity supported by in vitro mutagenicity
Carcinogenicity	1A	Known Human Carcinogen Based on human evidence
Reproductive toxicity	2	Human or animal evidence possibly with other information

GHS Hazards:

H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H341	Suspected of causing genetic defects
H350	May cause cancer
H361	Suspected of damaging fertility or the unborn child
UC Propositions	

GHS Precautions:

P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read and understood
P261	Avoid breathing dust/fume/gas/mist/vapours/spray
P264	Wash thoroughly after handling
P272	Contaminated work clothing should not be allowed out of the workplace
P280	Wear protective gloves/protective clothing/eye protection/face protection
P281	Use personal protective equipment as required
P310	Immediately call a POISON CENTER or doctor/physician
P321	Specific treatment (see label)
P362	Take off contaminated clothing and wash before reuse
P363	Wash contaminated clothing before reuse
P302+P352	IF ON SKIN: Wash with soap and water

P305+P351+P338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact

lenses if present and easy to do – continue rinsing

P308+P313 IF exposed or concerned: Get medical advice/attention P332+P313 If skin irritation occurs: Get medical advice/attention

P333+P313 If skin irritation or a rash occurs: Get medical advice/attention

P405 Store locked up

P501 Dispose of contents/container in accordance with all local, regional, national, and

international regulations.

Signal Word: Danger



Section 3 - Composition / Information on Ingredients

Chemical Name	CAS number	Weight Concentration %
Quartz	14808-60-7	50.00% - 60.00%
Bisphenol A diglycidyl ether resin	25068-38-6	20.00% - 30.00%
Alkyl c12 - c14 glycidyl ether	68609-97-2	5.00% - 10.00%
Hydrous magnesium silicate	14807-96-6	5.00% - 10.00%
Nonylphenol	84852-15-3	1.00% - 5.00%

Section 4 - First Aid Measures

Inhalation: If affected, remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.

Eye Contact: Immediately flush eyes for at least fifteen minutes with running water. Hold eyelids apart to ensure rinsing of the entire eye surface and lids with water. If eye irritation persists: Get medical advice/attention.

Skin contact: Immediately remove contaminated clothing and shoes. Wash affected areas thoroughly with soap and water. If irritation develops, seek medical attention.

Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious person. If a person vomits when lying on his back, place him in the recovery position. Get immediate medical attention.

Section 5 - Fire Fighting Measures

Flash Point: 208 C (406 F) LEL: UEL:

Extinguishing Media: Use carbon dioxide, foam, dry chemical, dry sand, water fog, or limestone powder extinguishing systems.

Unusual Fire and Explosion Hazards: None

Hazardous combustion products: Irritating or toxic substances may be emitted upon burning, combustion or decomposition. See section 10 (Stability and Reactivity) for additional information.

Special Fire Fighting Procedures: Firefighters should be equipped with self-contained breathing apparatus.

Fire Equipment: No Data

Section 6 - Accidental Release Measures

Spill And Leak Procedures: Avoid all personal contact. Ensure cleanup personnel wear all appropriate Personal Protective Equipment (PPE), including respiratory protection. Spills should be contained, solidified, and placed in suitable containers for disposal.

Section 7 - Handling and Storage

Handling Precautions: Use good laboratory/workplace procedures. Wash thoroughly after handling this product. Always wash up before eating, smoking or using the facilities. Use under well-ventilated conditions. Avoid eye and skin contact. Avoid inhalation of aerosol, mist, spray, fume or vapor. Avoid drinking, tasting, swallowing or ingesting this product. Wash contaminated clothing before reuse. Discard shoes contaminated with this product.

Storage Requirements: Keep away from heat, sparks, and open flames. Store cool and dry, under well-ventilated conditions. Store this material away from incompatible substances (see section 10). Do not store in open, unlabeled or mislabeled containers. Keep container closed when not in use.

Section 8 - Exposure Controls / Personal Protection

Chemical Name / CAS #	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Quartz 14808-60-7	TWA30 mg/m3 / %SiO2+2 total dust TWA: 10 mg/m3 /%SiO2+2 respirable fraction	TWA: 0.025 mg/m3	Not Established
Bisphenol A diglycidyl ether resin 25068-38-6	Not Established	Not Established	Not Established
Alkyl c12 - c14 glycidyl ether 68609-97-2	Not Established	Not Established	Not Established
Hydrous magnesium silicate 14807-96-6	TWA: 20 million particles per ft3	TWA: 2 mg/m3	Not Established
Nonylphenol 84852-15-3	Not Established	Not Established	Not Established

Ventilation: Good general mechanical ventilation and local exhaust is recommended.

Hygiene: Eye wash must be easily accessible. Wear protective clothing as necessary to prevent contact. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. Gloves must be inspected regularly and prior to each use. Replace if necessary.

Personal Protective Equipment: Wear impervious protective gloves. Wear OSHA, NIOSH approved organic vapor respirator if ventilation is inadequate. Wear appropriate protective eyewear such as splash-proof, chemical resistant safety goggles.

Contaminated Gear: Take off all contaminated clothing immediately. Wash contaminated clothing before reuse.

Section 9 - Physical and Chemical Properties

This mixture typically exhibits the following properties under normal circumstances:

AppearanceViscous liquidOdorNot Avaiilable

Physical State Liquid Vapor Density 5.08

Vapor Pressure 0.047 mm Hg **Boiling Range** 218 to 2230 °C

Specific Gravity (SG) 1.624 Lbs VOC/Gallon Less 0.00

Water

Section 10 - Stability and Reactivity

Stability:

STABLE

Components of this mixture are incompatible with the following materials:

Strong Oxidizers
Strong Acids
Strong Bases

Strong Reducing Agents

Amines

This mixture is likely to exhibit the following combustion products:

No Data

Hazardous polymerization will not occur.

Section 11 - Toxicological Information

Mixture Toxicity:

Component Toxicity:

68609-97-2 Alkyl c12 - c14 glycidyl ether

Oral LD50: 17 g/kg (rat) Dermal LD50: 4,500 mg/kg (rabbit)

84852-15-3 Nonylphenol

Oral LD50: 1,412 mg/kg (Rat) Dermal LD50: 2,031 mg/kg (Rabbit)

Routes of Entry:

Inhalation Skin Contact Eye Contact Ingestion

Exposure to this material may affect the following organs:

Lungs Respiratory System

The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing):

CAS Number	Description	<u>% Weight</u>	Carcinogen Rating
14808-60-7	Quartz	50% - 60%	Quartz: If product is in liquid or paste form, physical or health hazards listed related to dust are not considered significant. However, product may contain substances that could be potential hazards if caused to become airborne due to grinding, sanding or other abrasive processes.

Section 12 - Ecological Information

Component Ecotoxicity:

Quartz LC50 >10,000 mg/l fish 72h; EC50 7600 mg/L water flea 48h; EC50

440mg/L algae, 72h;

Bisphenol A diglycidyl ether resin LC50 3.1 mg/l fish 96h; EC50 2.1 mg/l water flea 48h; EC50 >11mg/l Algae

72h; LC50 >100mg/l bacteria 3h

Alkyl c12 - c14 glycidyl ether EC50 10 mg/l water flea 48h

Hydrous magnesium silicate LC50 >100 g/l fish

Nonylphenol LC50 0.209 mg/l fish 96h; EC50 0.0844 mg/l water flea 48h

Section 13 - Disposal Considerations

Waste disposal Methods: Dispose in accordance with Federal, State and Local regulations.

Section 14 - Transport Information

This material is classified for transport as follows:

<u>Agency Proper Shipping Name</u> <u>UN Number Packing Group Hazard Class</u>

DOT Paint Related Material, Corrosive 3066 III 8

IATA No Data

IMDG No Data

Section 15 - Regulatory Information

Additional regulatory listings, where applicable:

Country Regulation All Components Listed

EU Risk Phrases

Safety Phrase

Toxic Substances Control Act (TSCA): All chemicals except those listed below appear in the Toxic Substances Control Act Chemical Substance Inventory:

No Data

EPA SARA Title III Section 313 (40 CFR 372) compnenets above 'de minimum' level:

Section 16 - Other Information

For further information, please contact the Product Safety director. The information and recommendations contained herein are, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. All chemicals may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Final determination of suitability of the chemical is the sole responsibility of the user. Users of any chemical should satisfy themselves that the conditions and methods of use assure that the chemical is used safely. No representations or warranties, either expressed or implied of merchantability, fitness for a particular purpose, or any other nature, are made hereunder with respect to the information contained herein, or to the chemical to which the user refers.

Date Revised: 2023-05-04 Revision #: 0