

LiquaTile 1184 Hardener (Part B)

Safety Data Sheet (SDS)

Section 1 - Product and Company Identification

Trade Name: LiquaTile 1184 Hardener (All Versions)

Company:

Wolverine Coatings Corporation 5969 Highway 221 Roebuck, SC 29376 +1 (864) 587-3144

Product Use: Coatings

Product Code: LiquaTile 1184-000 UVR Hardener

Emergency Contact:

ChemTel 24 Hr. US Emergency Number:

+1 (800) 255-3924

ChemTel 24 Hr. Worldwide Emergency Number:

+1 (813) 248-0585

Not recommended for: None Identified

Section 2 - Hazards Identification

GHS Ratings:

Oral Toxicity	Acute	Oral>300+<=2000mg/kg
	Tox. 4	
Skin Corrosive	1B	Destruction of dermal tissue: Exposure < 1 hour Observation < 14
		days, visible necrosis in at least one animal
Eye Corrosive	1	Serious eye damage: Irreversible damage 21 days after exposure,
•		Draize score: Corneal opacity >= 3, Iritis > 1.5
Skin Sensitizer	1	Skin Sensitizer
Carcinogen	2	Limited evidence of human or animal carcinogenicity
Reproductive	2	Human or animal evidence possibly with other information
Toxin		,

GHS Hazards

H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H351	Suspected of causing cancer
H361	Suspected of damaging fertility or the unborn child
110 B 41	

<u>G</u>

ìŀ	IS Precautions	Suspected of during ing fortility of the driboth office
	P201	Obtain special instructions before use
	P202	Do not handle until all safety precautions have been read and understood
	P260	Do not breathe dust/fume/gas/mist/vapours/spray
	P261	Avoid breathing dust/fume/gas/mist/vapours/spray
	P264	Wash thoroughly after handling
	P270	Do not eat, drink or smoke when using this product
	P272	Contaminated work clothing should not be allowed out of the workplace
	P280	Wear protective gloves/protective clothing/eye protection/face protection
	P281	Use personal protective equipment as required
	P310	Immediately call a POISON CENTER or doctor/physician
	P321	Specific treatment (see label)
	P330	Rinse mouth
	P363	Wash contaminated clothing before reuse
	P301+P312	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
	P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
	P302+P352	IF ON SKIN: Wash with soap and water

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse

skin with water/shower

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable

for breathing

P305+P351+P338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact

lenses if present and easy to do – continue rinsing

P308+P313 IF exposed or concerned: Get medical advice/attention
P333+P313 If skin irritation or a rash occurs: Get medical advice/attention

P405 Store locked up

P501 Dispose of contents/container in accordance with all local, regional, national, and

international regulations.

Signal Word: Danger



Section 3 - Composition / Information on Ingredients

Chemical Name	CAS number	Weight Concentration %
Benzyl Alcohol	100-51-6	40.00% - 50.00%
Isophorone Diamine	2855-13-2	20.00% - 30.00%
Trade Secret		1.00% - 5.00%
Phenol, 4,4'-(1-methylethylidene)bis-	80-05-7	1.00% - 5.00%
Xylene	1330-20-7	1.00% - 5.00%
Ethylbenzene	100-41-4	0.10% - 1.00%

Section 4 - First Aid Measures

Inhalation: If affected, remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.

Eye Contact: Immediately flush eyes for at least fifteen minutes with running water. Hold eyelids apart to ensure rinsing of the entire eye surface and lids with water. If eye irritation persists: Get medical advice/attention.

Skin contact: Immediately remove contaminated clothing and shoes. Wash affected areas thoroughly with soap and water. If irritation develops, seek medical attention.

Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious person. If a person vomits when lying on his back, place him in the recovery position. Get immediate medical attention.

Section 5 - Fire Fighting Measures

Flash Point: 97 C (207 F) LEL: 1.00 UEL: 13.00

Extinguishing Media: Use carbon dioxide, foam, dry chemical, dry sand, water fog, or limestone powder extinguishing systems.

Unusual Fire and Explosion Hazards: None

Hazardous combustion products: Irritating or toxic substances may be emitted upon burning, combustion or decomposition. See section 10 (Stability and Reactivity) for additional information.

Special Fire Fighting Procedures: Firefighters should be equipped with self-contained breathing apparatus.

Fire Equipment: No Data

Section 6 - Accidental Release Measures

Spill And Leak Procedures: Avoid all personal contact. Ensure cleanup personnel wear all appropriate Personal Protective Equipment (PPE), including respiratory protection. Spills should be contained, solidified, and placed in suitable containers for disposal.

Section 7 - Handling and Storage

Handling Precautions: Use good laboratory/workplace procedures. Wash thoroughly after handling this product. Always wash up before eating, smoking or using the facilities. Use under well-ventilated conditions. Avoid eye and skin contact. Avoid inhalation of aerosol, mist, spray, fume or vapor. Avoid drinking, tasting, swallowing or ingesting this product. Wash contaminated clothing before reuse. Discard shoes contaminated with this product.

Storage Requirements: Keep away from heat, sparks, and open flames. Store cool and dry, under well-ventilated conditions. Store this material away from incompatible substances (see section 10). Do not store in open, unlabeled or mislabeled containers. Keep container closed when not in use.

Section 8 - Exposure Controls / Personal Protection

Chemical Name / CAS #	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Benzyl Alcohol 100-51-6	Not Established	Not Established	Not Established
Isophorone Diamine 2855-13-2	Not Established	Not Established	Not Established
Trade Secret	Not Established	Not Established	Not Established
Phenol, 4,4'-(1- methylethylidene)bis- 80-05-7	Not Established	Not Established	Not Established
Xylene 1330-20-7	Not Established	TWA: 100 ppm	Not Established
Ethylbenzene 100-41-4	TWA: 435 mg/m3	TWA: 20 ppm	Not Established

Ventilation: Good general mechanical ventilation and local exhaust is recommended.

Hygiene: Eye wash must be easily accessible. Wear protective clothing as necessary to prevent contact. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. Gloves must be inspected regularly and prior to each use. Replace if necessary.

Personal Protective Equipment: Wear impervious protective gloves. Wear OSHA, NIOSH approved organic vapor respirator if ventilation is inadequate. Wear appropriate protective eyewear such as splash-proof, chemical resistant safety goggles.

Contaminated Gear: Take off all contaminated clothing immediately. Wash contaminated clothing before reuse.

Section 9 - Physical and Chemical Properties

This mixture typically exhibits the following properties under normal circumstances:

Appearance:	Liquid	Odor:	Not available
Vapor Pressure:	0.47 mm Hg	Odor threshold:	Not available

Vapor Density: Not available pH: Not available Density (g/cm3): 1.04 Melting point: Not available Freezing point: Not available **Solubility:** Not available **Boiling range:** Not available Flash point: 97 C, 207 F **Evaporation rate:** Not available Flammability: Not available **Explosive Limits:** Not available Partition coefficient (n-Not available octanol/water): Autoignition Not available Decomposition Not available temperature: temperature: Viscosity: Not available Grams VOC less water: Not available

Section 10 - Stability and Reactivity

Stability:

STABLE

Components of this mixture are incompatible with the following materials:

Organic Acids

Mineral Acids

Strong Oxidizers

Peroxides

Sodium Hypochlorite

Strong Acids

Strong Bases

This mixture is likely to exhibit the following combustion products:

Carbon Dioxide, Carbon Monoxide

Nitrogen Oxides

Ammonia

Biphenyls

Hazardous polymerization will not occur.

Section 11 - Toxicological Information

Mixture Toxicity:

Oral Toxicity LD50: 1,765mg/kg Dermal Toxicity LD50: 2,749mg/kg Inhalation Toxicity LC50: 6mg/L

Component Toxicity:

100-51-6 Benzyl Alcohol

Oral LD50: 1,620 mg/kg (Rat) Dermal LD50: 2,010 mg/kg (Rabbit) Inhalation LC50: 4 mg/L (

2855-13-2 Isophorone Diamine

Oral LD50: 1,030 mg/kg (rat) Dermal LD50: 2,000 mg/kg (rat) Inhalation LC50: 5 mg/L (rat)

80-05-7 Phenol, 4,4'-(1-methylethylidene)bis-

Oral LD50: 5,000 mg/kg (rat) Inhalation LC50: 170 mg/m3 (rat)

1330-20-7 Xvlene

Oral LD50: 4,300 mg/kg (rat) Dermal LD50: 1,700 mg/kg (rabbit) Inhalation LC50: 5,000 ppr

100-41-4 Ethylbenzene

Oral LD50: 3,500 mg/kg (rat) Inhalation LC50: 17 mg/L (rat)

Routes of Entry:

Inhalation Skin Contact Eye Contact Ingestion

Exposure to this material may affect the following organs:

No Data

The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as

carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing):

CAS NumberDescription% WeightCarcinogen Rating100-41-4Ethylbenzene0.1 to 1.0%Ethylbenzene:

Section 12 - Ecological Information

Component Ecotoxicity:

Benzyl Alcohol LC50 460 mg/l fish 96 h; EC50 360 ppm water flea 48 h; EC50 640 mg/l

algae 96 h; EC10 658 mg/l bacteria 16 h

Isophorone Diamine LC50 110 mg/l fish 96h; ErC50 50 mg/l algae 72h; EC10 1120 mg/l bacteria

18h

Phenol, 4,4'-(1-methylethylidene)bis- LC50 4.6 mg/l fish 96h; EC50 10.2 mg/l water flea 48h; EC50 3.1 mg/l

algae 96h

Xylene LC50 2 mg/l fish 96h; EC50 75.49 mg/l water flea 24h; EC50 72 mg/l algae

14d

Ethylbenzene LC50 5.1 mg/l fish 96h; EC50 2.4 mg/l water flea 96h; EC50 4.9 mg/l algae

72h

Section 13 - Disposal Considerations

Waste disposal Methods: Dispose in accordance with Federal, State and Local regulations.

Section 14 - Transport Information

This material is classified for transport as follows:

Agency Proper Shipping Name UN Number Packing Group Hazard Class

DOT Paint Related Material, Corrosive 3066 III 8

IATA IMDG

Section 15 - Regulatory Information

Additional regulatory listings, where applicable:

State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

WARNING! This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

Ethylbenzene 100-41-4

Materials not included on the Canada DSL inventory:

- None

Commonwealth of Massachusetts "Right to Know": This product contains the following toxic or hazardous substances which appear on the Massachusetts Substance List:

Ethylbenzene 100-41-4 Xylene 1330-20-7

Phenol, 4,4'-(1-methylethylidene)bis- 80-05-7

Benzyl Alcohol 100-51-6

NJ "Right to Know": This product contains the following toxic or hazardous substances which appear on the New Jersey Substance List:

Ethylbenzene 100-41-4 Xylene 1330-20-7

Phenol, 4,4'-(1-methylethylidene)bis- 80-05-7

Benzyl Alcohol 100-51-6

Pennsylvania "Right to Know": This product contains the following toxic or hazardous substances which appear on the Pennsylvania Substance List:

Ethylbenzene 100-41-4 Xylene 1330-20-7 Phenol, 4,4'-(1-methylethylidene)bis- 80-05-7 Benzyl Alcohol 100-51-6

EPA SARA Title III Section 313 (40 CFR 372) components above 'de minimum' level:

Ethylbenzene 100-41-4 Xylene 1330-20-7 Phenol, 4,4'-(1-methylethylidene)bis- 80-05-7

Toxic Substances Control Act (TSCA): All chemicals except those listed below appear in the Toxic Substances Control Act Chemical Substance Inventory:

- None

Country Regulation All Components Listed

EU Risk Phrases

Safety Phrase

Toxic Substances Control Act (TSCA): All chemicals except those listed below appear in the Toxic Substances Control Act Chemical Substance Inventory:

- None

EPA SARA Title III Section 313 (40 CFR 372) compnenets above 'de minimum' level:

Section 16 - Other Information

For further information, please contact the Product Safety director. The information and recommendations contained herein are, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. All chemicals may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Final determination of suitability of the chemical is the sole responsibility of the user. Users of any chemical should satisfy themselves that the conditions and methods of use assure that the chemical is used safely. No representations or warranties, either expressed or implied of merchantability, fitness for a particular purpose, or any other nature, are made hereunder with respect to the information contained herein, or to the chemical to which the user refers.

Date Revised: 2019-11-25 Revision #: 4