



# ProtoCoat 1253 Resin

(Part A)

Safety Data Sheet (SDS)

## Section 1 - Product and Company Identification

**Trade Name:** ProtoCoat 1253 Resin (All Versions)

**Product Code:** ProtoCoat 1253-010 NEU Resin

**Company:**

Wolverine Coatings Corporation  
5969 Highway 221  
Roebuck, SC 29376  
+1 (864) 587-3144

**Emergency Contact:**

ChemTel 24 Hr. US Emergency Number:  
+1 (800) 255-3924  
ChemTel 24 Hr. Worldwide Emergency Number:  
+1 (813) 248-0585

**Product Use:** Coatings

**Not recommended for:** None Identified

## Section 2 - Hazards Identification

**GHS Ratings:**

Flammable Liquid	2	Flash point < 23°C and initial boiling point > 35°C (95°F)
Inhalation Toxicity	Acute Tox. 3	Gases >500+<=2500ppm, Vapors >2+<=10mg/l, Dusts & Mists >0.5+<=1mg/l
Carcinogen	1A	Known Human Carcinogen Based on human evidence
Organ Toxin Single Exposure	3	Transient target organ effects- Narcotic effects- Respiratory tract irritation
Organ Toxin Repeated Exposure	1	Significant toxicity in humans- Reliable, good quality human case studies or epidemiological studies Presumed significant toxicity in humans- Animal studies with significant and/or severe toxic effects relevant to humans at generally low exposure (guidanc

**GHS Hazards**

H225	Highly flammable liquid and vapour
H331	Toxic if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H350	May cause cancer
H372	Causes damage to organs through prolonged or repeated exposure

**GHS Precautions**

P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read and understood
P210	Keep away from heat/sparks/open flames/hot surfaces – No smoking
P233	Keep container tightly closed
P240	Ground/bond container and receiving equipment
P241	Use explosion-proof electrical/ventilating/light/equipment
P242	Use only non-sparking tools
P243	Take precautionary measures against static discharge
P260	Do not breathe dust/fume/gas/mist/vapours/spray
P261	Avoid breathing dust/fume/gas/mist/vapours/spray
P264	Wash thoroughly after handling
P270	Do not eat, drink or smoke when using this product
P271	Use only outdoors or in a well-ventilated area
P280	Wear protective gloves/protective clothing/eye protection/face protection
P281	Use personal protective equipment as required
P311	Call a POISON CENTER or doctor/physician

P312	Call a POISON CENTER or doctor/physician if you feel unwell
P314	Get Medical advice/attention if you feel unwell
P321	Specific treatment (see label)
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
P308+P313	IF exposed or concerned: Get medical advice/attention
P370+P378	In case of fire: Use carbon dioxide, alcohol-resistant foam, dry chemical, dry sand, or water fog for extinction
P405	Store locked up
P403+P233	Store in a well ventilated place. Keep container tightly closed
P403+P235	Store in a well ventilated place. Keep cool
P501	Dispose of contents/container in accordance with all local, regional, national, and international regulations.

**Signal Word:** Danger



### Section 3 - Composition / Information on Ingredients

Chemical Name	CAS number	Weight Concentration %
Quartz	14808-60-7	50.00% - 60.00%
Methyl Isobutyl Ketone	108-10-1	5.00% - 10.00%

### Section 4 - First Aid Measures

**Inhalation:** If affected, remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.

**Eye Contact:** Immediately flush eyes for at least fifteen minutes with running water. Hold eyelids apart to ensure rinsing of the entire eye surface and lids with water. If eye irritation persists: Get medical advice/attention.

**Skin contact:** Immediately remove contaminated clothing and shoes. Wash affected areas thoroughly with soap and water. If irritation develops, seek medical attention.

**Ingestion:** Do not induce vomiting. Never give anything by mouth to an unconscious person. If a person vomits when lying on his back, place him in the recovery position. Get immediate medical attention.

### Section 5 - Fire Fighting Measures

**Flash Point:** 14 C (57 F) LEL: 1.00 UEL: 8.00

**Extinguishing Media:** Use carbon dioxide, foam, dry chemical, dry sand, water fog, or limestone powder extinguishing systems.

**Unusual Fire and Explosion Hazards:** None

**Hazardous combustion products:** Irritating or toxic substances may be emitted upon burning, combustion or decomposition. See section 10 (Stability and Reactivity) for additional information.

**Special Fire Fighting Procedures:** Firefighters should be equipped with self-contained breathing apparatus.

**Fire Equipment:** No Data

### Section 6 - Accidental Release Measures

**Spill And Leak Procedures:** Avoid all personal contact. Ensure cleanup personnel wear all appropriate Personal Protective Equipment (PPE), including respiratory protection. Spills should be contained, solidified, and placed in suitable containers for disposal.

## Section 7 - Handling and Storage

**Handling Precautions:** Use good laboratory/workplace procedures. Wash thoroughly after handling this product. Always wash up before eating, smoking or using the facilities. Use under well-ventilated conditions. Avoid eye and skin contact. Avoid inhalation of aerosol, mist, spray, fume or vapor. Avoid drinking, tasting, swallowing or ingesting this product. Wash contaminated clothing before reuse. Discard shoes contaminated with this product.

**Storage Requirements:** Keep away from heat, sparks, and open flames. Store cool and dry, under well-ventilated conditions. Store this material away from incompatible substances (see section 10). Do not store in open, unlabeled or mislabeled containers. Keep container closed when not in use.

## Section 8 - Exposure Controls / Personal Protection

Chemical Name / CAS #	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Quartz 14808-60-7	TWA: 30 mg/m <sup>3</sup> / %SiO <sub>2</sub> +2 total dust TWA: 10 mg/m <sup>3</sup> /%SiO <sub>2</sub> +2 respirable fraction	TWA: 0.025 mg/m <sup>3</sup>	Not Established
Methyl Isobutyl Ketone 108-10-1	TWA: 205 mg/m <sup>3</sup> ; STEL: 300 mg/m <sup>3</sup>	STEL: 75ppm; TWA (TLV): 20 ppm	Not Established

**Ventilation:** Good general mechanical ventilation and local exhaust is recommended.

**Hygiene:** Eye wash must be easily accessible. Wear protective clothing as necessary to prevent contact. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. Gloves must be inspected regularly and prior to each use. Replace if necessary.

**Personal Protective Equipment:** Wear impervious protective gloves. Wear OSHA, NIOSH approved organic vapor respirator if ventilation is inadequate. Wear appropriate protective eyewear such as splash-proof, chemical resistant safety goggles.

**Contaminated Gear:** Take off all contaminated clothing immediately. Wash contaminated clothing before reuse.

## Section 9 - Physical and Chemical Properties

This mixture typically exhibits the following properties under normal circumstances:

<b>Appearance:</b> Liquid	<b>Odor:</b> Not available
<b>Vapor Pressure:</b> 15.0 mm Hg	<b>Odor Threshold:</b> Not available
<b>Vapor Density:</b> Not available	<b>pH:</b> Not available
<b>Density (g/cm<sup>3</sup>):</b> 1.63	<b>Melting Point:</b> Not available
<b>Freezing Point:</b> Not available	<b>Solubility:</b> Not available
<b>Boiling Range:</b> Not available	<b>Flash Point:</b> 14 C, 57 F
<b>Evaporation Rate:</b> Not available	<b>Flammability:</b> Not available
<b>Explosive Limits:</b> Not available	<b>Partition Coefficient (n-octanol/water):</b> Not available
<b>Autoignition Temperature:</b> Not available	<b>Decomposition Temperature:</b> Not available
<b>Viscosity:</b> Not available	<b>Grams VOC (less water):</b> Not available

## Section 10 - Stability and Reactivity

### Stability:

STABLE

### Components of this mixture are incompatible with the following materials:

Strong Oxidizers  
Strong Bases

### This mixture is likely to exhibit the following combustion products:

No Data

Hazardous polymerization will not occur.

## Section 11 - Toxicological Information

### Mixture Toxicity:

Inhalation Toxicity LC50: 1mg/L

### Component Toxicity:

108-10-1 Methyl Isobutyl Ketone  
Oral LD50: 2,080 mg/kg (rat) Inhalation LC50: 16 mg/m<sup>3</sup> (rat)

### Routes of Entry:

Inhalation Skin Contact Eye Contact Ingestion

### Exposure to this material may affect the following organs:

Lungs Respiratory System

The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing):

<u>CAS Number</u>	<u>Description</u>	<u>% Weight</u>	<u>Carcinogen Rating</u>
14808-60-7	Quartz	50 to 60%	Quartz: If product is in liquid or paste form, physical or health hazards listed related to dust are not considered significant. However, product may contain substances that could be potential hazards if caused to become airborne due to grinding, sanding or other abrasive processes.
108-10-1	Methyl Isobutyl Ketone	5 to 10%	Methyl Isobutyl Ketone: Suspected of causing cancer.

## Section 12 - Ecological Information

### Component Ecotoxicity:

Quartz LC50 >10,000 mg/l fish 72h;

Methyl Isobutyl Ketone LC50 480 mg/l fish 48h; EC50 3623 mg/l water flea 24h; EC50 2000 mg/l algae 48h

## Section 13 - Disposal Considerations

**Waste disposal Methods:** Dispose in accordance with Federal, State and Local regulations.

## Section 14 - Transport Information

This material is classified for transport as follows:

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
DOT	Paint	1263	II	3
IATA	No Data			
IMDG	No Data			

## Section 15 - Regulatory Information

### Additional regulatory listings, where applicable:

#### State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

WARNING! This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

Methyl Isobutyl Ketone 108-10-1  
Quartz 14808-60-7

#### Materials not included on the Canada DSL inventory:

- None

**Commonwealth of Massachusetts "Right to Know":** This product contains the following toxic or hazardous substances which appear on the Massachusetts Substance List:

Methyl Isobutyl Ketone 108-10-1  
Quartz 14808-60-7

**NJ "Right to Know":** This product contains the following toxic or hazardous substances which appear on the New Jersey Substance List:

Methyl Isobutyl Ketone 108-10-1  
Quartz 14808-60-7

**Pennsylvania "Right to Know":** This product contains the following toxic or hazardous substances which appear on the Pennsylvania Substance List:

Methyl Isobutyl Ketone 108-10-1  
Quartz 14808-60-7

#### EPA SARA Title III Section 313 ( 40 CFR 372) components above 'de minimum' level:

Methyl Isobutyl Ketone 108-10-1

**Toxic Substances Control Act (TSCA):** All chemicals except those listed below appear in the Toxic Substances Control Act Chemical Substance Inventory:

- None

<u>Country</u>	<u>Regulation</u>	<u>All Components Listed</u>
----------------	-------------------	------------------------------

### EU Risk Phrases

#### Safety Phrase

Toxic Substances Control Act (TSCA): All chemicals except those listed below appear in the Toxic Substances Control Act Chemical Substance Inventory:

- None

EPA SARA Title III Section 313 ( 40 CFR 372) components above 'de minimum' level:

## Section 16 - Other Information

For further information, please contact the Product Safety director. The information and recommendations contained herein are, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. All chemicals may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Final determination of suitability of the chemical is the sole responsibility of the user. Users of any chemical should satisfy themselves that the conditions and methods of use assure that the chemical is used safely. No representations or warranties, either expressed or implied of merchantability, fitness for a particular purpose, or any other nature, are made hereunder with respect to the information contained herein, or to the chemical to which the user refers.

Date revised: 2019-11-25

Revision #: 1