

# **PRODUCT DESCRIPTION**

SpheriTex 0110 is a spherical glass aggregate for resinous coating systems. The resulting slip-resistance is light and easily cleanable due to SpheriTex 0110's round, rather than angular profile.

#### **APPLICATION DATA SUMMARY**

SpheriTex 0110 is mixed or broadcast into resinous systems as indicated in the Technical Data Sheet for the desired coating system.

# SIZING AVAILABILITY

SpheriTex 0110-120	120 microns (median)
SpheriTex 0110-250	250 microns (median)

# SAFETY PRECAUTIONS

Read the Safety Data sheet carefully before use. Safety precautions in the SDS should be carefully followed during storage, handling and use. Improper use and handling can be hazardous to health and cause fire or explosion. For further information, please refer to our "Epoxy Resin Safety Handling Guide".

# **APPLICATION DATA**

Substrate:	Consult the Technical Data Sheet of the desired coating system for recommendations.
Substrate Preparation:	Consult the Technical Data Sheet of the desired coating system for recommendations.
Application Instructions:	Consult the Technical Data Sheet of the desired coating system for recommendations.

## **PHYSICAL DATA**

Color:	Clear
Components:	One
Volume Solids:	100%
VOC:	None

#### LIMITATIONS

• SpheriTex 0110 can settle or sink when mixed or broadcasted into lower density coatings. Keep mixed well

• SpheriTex 0110 can be pressed into a roller nap which can yield an uneven texture. Keep mixture agitated and do not press roller nap to the bottom of mixture where settling may have occured

## **MIX RATIOS WITH ENDURASHIELD 2254**

EnduraShield 2254	Spheritex 0110-120
1.25 Gallon Kit	8 fl oz.
By Volume	
10	1

#### **SHIPPING DATA**

Packaging :	8 oz., 50 lbs. Bags
Shelf Life (indoors @ 40-100oF):	24 Months

#### SAFETY

For your safety, all required personal protection equipment should be used when operating machinery or handling chemicals. Concrete dust is a source of silica particles and other hazardous materials that can cause silicosis and other illnesses. Proper safety equipment and methods are the responsibility of the installation company, general contractor, and/or facility owner.

#### WARRANTY

Wolverine Coatings Corporation warrants its products to be free from defects in material and workmanship. Wolverine Coatings Corporation's sole obligation and Buyer's exclusive remedy in connection with the products shall be limited, at Wolverine Coatings option, to either replacement of products not conforming to this Warranty or credit to the Buyer's account in the invoiced amount of the nonconforming products. Any claim under this warranty must be made by the Buyer to Wolverine Coatings in writing within five (5) days of Buyer's discovery of the claimed defect, but in no event later than the expiration of the applicable shelf life, or one year from the ship date, whichever is earlier. Buyer's failure to notify Wolverine Coatings of such nonconformance as required herein shall bar Buyer from recovery under this warranty.

Wolverine Coatings makes no other warranties about the product. No other warranties, whether expressed, implied, or statutory, such as warranties of merchantability or fitness for a particular purpose, shall apply.

Any recommendation or suggestion relating to the use of the products made by Wolverine Coatings, whether in its technical literature, or in response to specific inquiry or otherwise, is based on data believed to be reliable; however, the products and information are intended for use by Buyers having requisite skill and know-how in the industry, and therefore it is for the Buyer to satisfy itself of the suitability of the products for its own particular use and it shall be deemed that Buyer has done so, at its sole discretion and risk. Variation in environment, changes in procedure of use, or extrapolation of data may cause unsatisfactory results.

#### LIMITATION OF LIABILITY

Wolverine Coatings Corporation's liability on any claims based upon Wolverine Coatings Corporation's negligence or strict liability, for any loss or damage arising out of, connected with, or resulting from the use of the products, shall in no case exceed the purchase price allocable to the products or parts thereof which give rise to the claim. In no event shall Wolverine Coatings Corporation be liable for consequential or incidental damages.

#### LITERATURE REVISION - TDS: SpheriTex 0110 - Rev. 230112

Published literature is subject to change without notice. Wolverine Coatings Corporation is constantly engaged in the testing of existing formulations, the development of new innovative technologies, and the evaluation of the latest practices. The latest literature should always be consulted at www.wolverinecoatings.com.



Wolverine Coatings Corporation 5969 Highway 221 | Roebuck, SC 29376 Tel: (864) 587-3144 | Fax: (864) 587-3147 e-mail: Sales@WolverineCoatings.com website: www.WolverineCoatings.com