

WearResist 0105-063

Aggregate for Increased Wear Resistance Technical Data Sheet (TDS)

PRODUCT DESCRIPTION

WearResist 0105 is a high-density aggregate that can be added to resinous coating systems. The small particle size of this additive helps impart increased resistance to wear due to heavy traffic. WearResist 0105 can also be added to lower the gloss of the coating.

APPLICATION DATA SUMMARY

WearResist 0105-063 is mixed or broadcast into resinous systems as indicated in the Technical Data Sheet for the desired coating system.

SIZING AVAILABILITY

WearResist 0105-063 63 microns (median)

SAFETY PRECAUTIONS

Read the Safety Data sheet carefully before use. Safety precautions in the SDS should be carefully followed during storage, handling and use. Improper use and handling can be hazardous to health and cause fire or explosion. For further information, please refer to our "Epoxy Resin Safety Handling Guide".

APPLICATION DATA

Substrate:	Consult the Technical Data Sheet of the desired coating system for recommendations.
Substrate Preparation:	Consult the Technical Data Sheet of the desired coating system for recommendations.
Application Instructions:	Consult the Technical Data Sheet of the desired coating system for recommendations.

PHYSICAL DATA

Color:	Clear / White
Components:	One
Volume Solids:	100%
VOC:	None

LIMITATIONS

- WearResist 0105-063 can settle or sink when mixed or broadcasted into lower density coatings. Keep mixed well
- WearResist 0105-063 can be pressed into a roller nap which can yield an uneven texture. Keep mixture agitated and do not press roller nap to the bottom of mixture where settling may have occured

SUGGESTED MIX RATIOS WITH ENDURASHIELD 2254

EnduraShield 2254	WearResist 0105-063
1.25 Gallon Kit	1 Quart
By Volume	
5	1

SHIPPING DATA

Packaging :	1.65 lbs. Bags, 3.29 lbs. Bags
Shelf Life (indoors @ 40-100oF):	24 Months

SAFETY

For your safety, all required personal protection equipment should be used when operating machinery or handling chemicals. Concrete dust is a source of silica particles and other hazardous materials that can cause silicosis and other illnesses. Proper safety equipment and methods are the responsibility of the installation company, general contractor, and/or facility owner.

WARRANTY

Wolverine Coatings Corporation warrants its products to be free from defects in material and workmanship. Wolverine Coatings Corporation's sole obligation and Buyer's exclusive remedy in connection with the products shall be limited, at Wolverine Coatings option, to either replacement of products not conforming to this Warranty or credit to the Buyer's account in the invoiced amount of the nonconforming products. Any claim under this warranty must be made by the Buyer to Wolverine Coatings in writing within five (5) days of Buyer's discovery of the claimed defect, but in no event later than the expiration of the applicable shelf life, or one year from the ship date, whichever is earlier. Buyer's failure to notify Wolverine Coatings of such nonconformance as required herein shall bar Buyer from recovery under this warranty.

Wolverine Coatings makes no other warranties about the product. No other warranties, whether expressed, implied, or statutory, such as warranties of merchantability or fitness for a particular purpose, shall apply.

Any recommendation or suggestion relating to the use of the products made by Wolverine Coatings, whether in its technical literature, or in response to specific inquiry or otherwise, is based on data believed to be reliable; however, the products and information are intended for use by Buyers having requisite skill and know-how in the industry, and therefore it is for the Buyer to satisfy itself of the suitability of the products for its own particular use and it shall be deemed that Buyer has done so, at its sole discretion and risk. Variation in environment, changes in procedure of use, or extrapolation of data may cause unsatisfactory results.

LIMITATION OF LIABILITY

Wolverine Coatings Corporation's liability on any claims based upon Wolverine Coatings Corporation's negligence or strict liability, for any loss or damage arising out of, connected with, or resulting from the use of the products, shall in no case exceed the purchase price allocable to the products or parts thereof which give rise to the claim. In no event shall Wolverine Coatings Corporation be liable for consequential or incidental damages.

LITERATURE REVISION - TDS: WearResist 0105-063 - Rev. 200716

Published literature is subject to change without notice. Wolverine Coatings Corporation is constantly engaged in the testing of existing formulations, the development of new innovative technologies, and the evaluation of the latest practices. The latest literature should always be consulted at www.wolverinecoatings.com.



Wolverine Coatings Corporation

5969 Highway 221 | Roebuck, SC 29376 Tel: (864) 587-3144 | Fax: (864) 587-3147 e-mail: sales@WolverineCoatings.com website: www.WolverineCoatings.com